



ANTI-SEIZE TECHNOLOGY
A.S.T. Industries, Inc.

SILVER ZINC™ COLD GALVANIZING SPRAY

Aerosol

SAFETY DATA SHEET

Section 1- Product and Company Identification

Product Code: 17044

Manufacture/Supplier : Anti-Seize Technology
2345 N. 17th Ave.
Franklin Park, IL 60131

Phone: 847-455-2300

Fax: 847-455-2371

Web: antiseize.com

Emergency Phone, 24 hr: Infotrac @ 1-800-535-5053 (US & Canada)
1-352-323-3500 (International)
Web: infotrac.net

Product Use: Galvanizing Spray

Restriction of Use: Only as directed

Date: May 19, 2015

Section 2-Hazard Identification

GHS Classification (Hazcom 2012):

Flammable aerosol—Category 1
Gas under pressure—Compressed Gas
Acute Toxicity-Dermal—Category 4
Acute Toxicity—Inhalation—Category 4
Skin Corrosion/Irritation—Category 2
Serious Eye Damage/Irritation—Category 2
Carcinogenicity—Category 2
Specific Organ Toxicity (single exposure)—Category 3

Label Elements:



Signal word: DANGER

Hazard Phrases:

H222—Extremely flammable aerosol
H280—Contains gas under pressure, may explode if heated
H312—Harmful in contact with skin
H332—Harmful if inhaled
H304—May be fatal if swallowed and enters airways

H336—May cause drowsiness or dizziness
H316—Causes mild skin irritation
H320—Causes eye irritation
H351—Suspected of causing cancer

Precautionary Phrases: Prevention

P201—Obtain special instructions before use
P202—Do not handle until all safety precautions have been read and understood
P280—Wear protective gloves/protective clothing/ eye protection/face protection
P264—Wash hands and face thoroughly after handling
P261—Avoid breathing dust/fume/gas/mist/vapors/spray
P271—Use only outdoors or in a well ventilated area
P210—Keep away from heat/sparks/open flames/ hot surfaces. No smoking
P211—Do not spray on an open flame or other ignition source
P251—Pressurized container. Do not pierce or burn, even after use.

Precautionary Phrases: Response:

P302—IF ON SKIN: Wash with soap and water
P305—IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing.
P301+310—IF SWALLOWED: Immediately call a POISON CENTER
P331—Do NOT induce vomiting.
P337—If eye irritation persists: Get medical advice/attention.
P308—IF exposed or concerned: Get medical advice/attention
P332—If skin irritation occurs: Get medical advice/attention
P337—If eye irritation persists: Get medical advice/attention
P362—Take off contaminated clothing and wash before reuse
P312—Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

P405—Store locked up
P410+403—Protect from sunlight. Store in a well ventilated place.
P410+412—Protect from sunlight. Do not expose to temperatures exceeding 50C/122F

Disposal:

P501--Dispose of contents in accordance with local, regional and national regulations.
Other Hazards: Toxic to aquatic life with long lasting effects

Section 3- Composition/ Information on Ingredients

CHEMICAL	CAS NUMBER	PERCENT
ACETONE	67-64-1	40-50
PROPANE/ISOBUTANE/n-BUTANE	68476-86-8	20-30
ZINC POWDER	7440-66-6	10-20
XYLENE	1330-20-7	1-10
ETHYL BENZENE	100-41-4	1-10
ALIPHATIC PETROLEUM DISTILLATES	64742-89-8	1-10

The specific identity and/or exact percentage of composition has been withheld as a trade secret

Section 4 – First Aid Measures

Eye: Immediately flush eyes with water, holding the eyelids apart. Get medical attention if irritation develops or persists.

Skin: In case of contact, wash thoroughly with plenty of water. Get medical attention if irritation persists.

Inhalation: Remove to fresh air and keep comfortable for breathing. If irritation occurs, get medical attention.

Ingestion: Aspiration Hazard. DO NOT induce vomiting. Get immediate medical attention.

Most Important symptoms and effects, both acute and delayed: Causes eye and skin irritation. Product is an aspiration hazard. May enter the lungs during swallowing or vomiting and cause lung damage. Inhalation may cause irritation, headache, dizziness and drowsiness.

Indication of any immediate medical attention and special treatment needed: Immediate medical attention required for ingestion.

Section 5 – Fire Fighting Measures

Suitable and Unsuitable Extinguishing Media: Use water spray or fog, foam, carbon dioxide or dry chemical.

Special Hazards Arising from the Chemical: Extremely flammable aerosol. Keep away from heat and open flames. Container may rupture or explode in the heat of a fire. Prolonged exposure to temperatures above 120°F may cause cans to burst. Combustion may produce carbon dioxide, carbon monoxide.

Special Equipment and Precautions for Fire-Fighters: Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water. Protect against bursting cans.

Section 6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Wear appropriate personal protective equipment. Eliminate all sources of ignition with explosion-proof equipment. Ventilate area.

Environmental Hazards: Report spills and releases as required to appropriate authorities.

Methods and Material for Containment and Cleaning Up: Place leaking container into a suitable container and place in a well-ventilated area until the propellant has dissipated. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal.

Section 7 – Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid breathing vapors and mists. Use with adequate ventilation. Keep away from heat sources. Contents under pressure. Do not puncture or incinerate container. Do not smoke while using.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, well-ventilated area at temperatures below 120°F. Do not store in direct sunlight.

Section 8 – Exposure Controls / Personal Protection

CHEMICAL NAME	EXPOSURE LIMITS
---------------	-----------------

ACETONE	500 ppm TWA ACGIH TLV 750 ppm STEL ACGIH TLV 1000 ppm TWA OSHA PEL
PROPANE/ISOBUTANE/n-BUTANE	1000ppm ACGIH TLV
ZINC POWDER	5mg/m3, OSHA PEL, as dust 10mg/m3, ACGIH TLV, as dust
XYLENE	100ppm, OSHA PEL 100ppm ACGIH TLV
ETHYL BENZENE	100ppm, OSHA TWA, 8 hrs. 100ppm ACGIH TWA, 8 hrs.

Appropriate Engineering Controls: Use with adequate general or local exhaust ventilation to maintain exposure levels below the exposure limits. If the product is used at high temperatures, local exhaust ventilation may be required.

Individual Protection Measures:

Respiratory Protection: In operations where the occupational exposure limits are exceeded, a NIOSH approved respirator with organic vapor/particulate cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin Protection: Impervious gloves such as rubber or nitrile recommended where needed to avoid prolonged skin contact .

Eye Protection: Safety glasses or goggles recommended where needed to avoid eye contact.

Section 9 – Physical and Chemical Properties

Appearance: silver gray aerosol	Vapor Density (air = 1): heavier than air
Odor: solvent like until dry	Specific Gravity: 1.23
Odor Threshold: Not established	Water Solubility: Not soluble
pH: Not available	Octanol/Water Partition Coefficient: Not available
Melting Point/Freezing Point: No data	Autoignition Temperature: Not available
Boiling Point: No data	Decomposition Temperature: Not available
Flash Point: Not determined	Viscosity: Not available
Evaporation Rate: slower than ether	Explosion Properties: None
Flammable Limits: LEL: Not established UEL: Not established	Oxidizing Properties: Not oxidizing

Vapor Pressure: Not established	Aerosol Fire Protection Level: 3
--	---

Section 10 – Stability and Reactivity

Reactivity: Not reactive under normal conditions of use.

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: None known

Conditions to Avoid: Use with strong oxidizing chemicals such as concentrated acids.

Incompatible Materials: Avoid strong oxidizing agents and acids.

Hazardous Decomposition Products: The thermal decomposition products are highly dependent upon the combustion conditions. Noxious or toxic fumes may be generated, some of which may be toxic or irritating.

Section 11 – Toxicological Information

Long term Toxicological studies have not been conducted for this product

Potential Health Effects:

Eye: May cause mild irritation.

Skin: Prolonged contact may cause mild irritation of the skin.

Inhalation: No adverse effects expected at ambient temperatures. Inhalation of vapors and fumes from thermal decomposition may cause respiratory irritation .

Ingestion: Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea

Chronic Hazards: Prolonged inhalation of thermal decomposition products may result in lung damage.

Carcinogen Status: None of the components of this product are listed as carcinogens by IARC, NTP or OSHA.

Section 12 – Ecological Information

Long term ecological studies have not been conducted for this product

Ecotoxicity: No Data

Bioaccumulative Potential: No Data

Mobility in Soil: No Data

Other Adverse Effects: No Data

Section 13 – Disposal Consideration

Waste disposal: Dispose of in a responsible manner. Follow local, state and federal guidelines. Do not discharge into sewers or waterways. Incineration is the preferred method of disposal, although it may be landfilled at an approved facility.

Section 14- Transport Information

DOT Proper Shipping Name: UN1950, Aerosols, 2.1, Limited Quantity

DOT Technical Name: None

DOT Hazard Class: 2.1

UN Number: UN1950

DOT Labels Required (49CFR172.101): LTD QTY

IMDG Shipping Description: UN1950, Aerosols, 2.1, FP -17 C, Limited Quantity, Marine Pollutant

ID Number: UN1950

Hazard Class: 2.1

Packing Group: None

Labels Required: None

Marking Required: Limited Quantity Mark

Placards Required: Limited Quantity and Marine Pollutant Mark On Transport Containers

ICAO/IATA

Proper shipping name: Aerosol, Flammable

Hazard Class: 2.1

Identification Number: UN 1950

Packing Group: None

Section 15 – Regulatory Information

Safety, health, and environmental regulations specific for the product in question.

CERCLA Hazardous Substances (Section 103)/RQ:

SARA Hazard Category (311/312): Fire Hazard, Pressure Hazard, Acute Health

SARA 313: This product contains the following chemicals regulated under SARA Title III, section 313: None

EPA TSCA Inventory: All of the components of this product are listed on the TSCA inventory.

CALIFORNIA PROPOSITION 65: This product is not known to contain listed chemicals.

Section 16 – Other Information:

The information contained herein is based on data considered accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results obtained from the use of his product. Therefore, because the product may be used under conditions beyond our control, we assume no liability for its use.