FIREPLUMB MACHINERY	FPS	
MACHINE PRODUCT RANGE	CODE	FIREPLUMB SUPPLIES
ROLL GROOVER 1"-12" Motor: 1100w induction type Speed: 24 RPM Roller Set: 1", 1 1/4"-1 1/2", 2"-6", 8"-12" Net weight: 140kg including a pipe support Grooving capacity: Sch10 1"-12", Sch40 1"-6"	CODE: 800004 YG12D	
POWERED PIPE CUTTER 2"-8" Motor: 550w induction type Speed: 24 RPM standard cutting wheel: for pipe 2"-6" Sch 10 /40,8" Sch 10 net weight: 70kg including a pipe support standard alloy cutting blade, HSS blade optional	CODE: 800006 QG8C-A	
POWERED PIPE CUTTER 2 1/2"-12" Motor: 750w induction type Speed: 24 RPM standard cutting wheel: for pipe 2 1/2"-6" Sch 10 /40,8" Sch 10 net weight: 71kg including a pipe support standard alloy cutting blade, HSS blade optional	CODE: 800007 QG12C	
HINGED PIPE CUTTER 1. Designed for rapid cutting of 1" through 14" steel pipes. 2. The cutters operate with minimal cutting rotation (90-110 degree), suitable for tight quarters. 3. During cutting operation, there is no sparks, serving jobs with such special requirements. 4. Portable and lightweight, easy for transportation	CODE: 800008 HS4 CODE: 800009 HS6 CODE: 800010 HS8	H4S H6S H8S
PIPE STAND DUAL BALL	CODE: 800013 1107A	Ž.
MANUAL HAND GROOVER CAN BE ATTACHED TO A POWER DRIVE	CODE: 800005 TWG11A	THE TAME

FIREPLUMB MACHINERY		FPS
MACHINE PRODUCT RANGE	CODE	FIREPLUMB SUPPLIES
THREADING MACHINE 1/2"-2" Motor: 1500w universal type Speed: 38 RPM die head (1/2"-2"): quick-open type, 811A Chuck: Hammer type with replaceable, rocker-action jaw inserts Rear centering device: Cam action Net Weight: 80KG (including accessories) Standard equipment including: 1206 tri-stand, 418 oiler, foot switch CE & CSA certified standard HSS dies	CODE: 800000 SQ50D	
ROLL GROOVING ATTACHMENT 2"-12" POWERED TO SUIT SQ50D	CODE: 800002 YG12A	
ROLL GROOVING ATTACHMENT 1 1/4"-6" MANUAL TO SUIT SQ50D	CODE: 800003 GC02	
MANUAL TEST BUCKET Testing range: 0-60bar(860psi, 6Mpa) • Tank capacity: 12L • Volume/stroke: ≈45ml • Connections: 1/2" BSPP • Accessories: pressure hose, pressure gauge, seal set	CODE: 800011 HSY30-5	TO VOLUMENT
ELECTRIC TEST PUMP Testing range: 0-60bar(860psi, 6Mpa) Water flow: 2.9L/min Valve: brass, single type Connections: 1/2" BSPP Power: 250W induction type Accessories: pressure hose, pressure gauge, seal set	CODE: 800014 DSY60	
OILER BUCKET For manual oiling required applications Hand-operating, easy pumping trigger. Oil is filtered and recirculated through reservior	CODE: 800012 418	
PORTABLE POWER DRIVE Motor: 1350w, universal Speed: 32 RPM Threading Capacity 1/2"- 2"	CODE: 800015 SQ30-2B	